Material Safety Data Sheet



MSDS #: 80307

SECTION I - PREPARATION INFORMATION

MSDS #: 80307 PREPARED BY: Compliance Department

DATE OF PREPARATION: 08/07/2014 BonaKemi USA, Inc.

LAST REVISION DATE: 8/29/2011 2550 S. Parker Rd., Suite 600

EMERGENCY CONTACT: 24-Hour Emergency Telephone Number Aurora, Colorado 80014

International: 1-703-527-3887 (Chemtrec) (303) 371-1411

SECTION II - PRODUCT IDENTIFICATION

PRODUCT NAME: BONA TRAFFIC® (COMMERCIAL GLOSS, COMMERCIAL SEMI-GLOSS, COMMERCIA

PRODUCT DESCRIPTION: WATERBORNE WOOD FLOOR FINISH

SECTION III - HAZARDOUS INGREDIENTS						
INGREDIENT	CAS#	% WEIGHT	TWA	LD-50(oral-rat)	LC-50(/hr, rat)	
2,6,8-TRIMETHYL-4-NONYLPOLYETHYLENE GLYCOL ETHER	60828-78-6	1-2.5%	NE	NE	NE	
DIPROPYLENE GLYCOL MONOMETHYL ETHER	34590-94-8	2.5-10%	100 PPM	8000 mg/kg	N/A	

SECTION IV - PHYSICAL DATA

BOILING RANGE: >212F (100C) **EVAPORATION RATE:** Slower than n-butyl acetate

WOLATILE - WT: 66 **DENSITY:** 8.66 LBS/GAL (1.04KG/L)

VAPOR DENSITY: Heavier than air SOLUBILITY IN WATER: Miscible

pH: 8.0

PRODUCT CHARACTERISTICS: White, milky liquid with a slight ammonia odor

SECTION V - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: Non-Flammable

FLASH POINT: None

% OF VOL. OF FLAMMABLE LIMITS (Upper): N/A (Lower): N/A

EXTINGUISHING MEDIA: Water Spray, Foam, Carbon Dioxide, Dry Chemical

UNUSUAL FIRE EXPLOSION HAZARDS:

Closed containers may explode (due to the build up of steam pressure) when exposed to extreme heat

SPECIAL FIREFIGHTING PROCEDURES:

Water may be used to cool containers to prevent pressure build-up. In emergency conditions or IDLH (Immediately Dangerous to Life or Health) atmospheres, use a NIOSH-approved, positive pressure, self-

contained breathing apparatus or full facepiece airline respirator.

Material Safety Data Sheet



MSDS #: 80307

SECTION VI - HEALTH HAZARD DATA AND FIRST AID PROCEDURES

EYE CONTACT: May cause irritation, redness and tearing. In case of contact, flush immediately with large amounts of

water and obtain medical attention

SKIN CONTACT: Prolonged or repeated contact may cause drying of skin. In case of contact, remove contaminated

clothing. Wash area with soap and water.

INHALATION: Excessive inhalation of vapors may cause dizziness and possible headache. If affected by inhalation,

remove to fresh air.

INGESTION: May cause gastrointestinal irritation and nausea. If swallowed, drink 1 or 2 glasses of water to dilute.

Get medical attention.

PRIMARY ROUTES OF ENTRY: Inhalation and Dermal

SECTION VII- TOXICOLOGICAL PROPERTIES

TOXICITY DATA: No ingredients in this product are listed by OSHA, IARC or NTP as a carcinogen, teratogen,

mutagen, or as having toxic reproductive effects. See Section II for exposure limits. See Section IX

for preventative measures.

SECTION VIII - REACTIVITY DATA

STABILITY: Stable REACTIVITY WITH WATER: Will not Occur HAZARDOUS DECOMPOSITION Usual products of combustion, e.g. Carbon Monoxice,

PRODUCTS: Carbon Dioxide, Nitrogen Oxides

HAZARDOUS POLYMERIZATION: Will Not Occur INCOMPATIBILITY Strong Oxidizers

(MATERIALS TO AVOID):

SECTION IX - PREVENTIVE MEASURES

WHMIS CLASSIFICATION: D-2

RESPIRATORY PROTECTION: PRODUCT NOT INTENDED FOR SPRAY APPLICATIONS. In areas where TLV is

exceeded, use a NIOSH-approved, properly fitted, air-purifying respirator with organic

vapor cartridges.

VENTILATION: Use with adequate general and/or local ventilation to maintain exposure level below TLV.

PROTECTIVE GLOVES: Wear chemical-resistant gloves such as nitrile rubber.

EYE PROTECTION: Use chemical splash goggles or OSHA-permitted safety glasses. Have an eyewash station

available.

OTHER PROTECTIVE

EQUIPMENT:

Wear impervious clothing to avoid repeated or prolonged skin contact.

HYGIENIC PRACTICES: Wash hands with soap and water before eating or using rest rooms.

IN CASE MATERIAL IS Ventilate area. Remove with inert absorbent.

RELEASED OR SPILLED:

WASTE DISPOSAL: Dispose of contaminated absorbent, container and unused contents in accordance with local,

state/provincial and federal regulations.

SHIPPING INFORMATION: Not regulated as a DOT hazardous material

Material Safety Data Sheet



MSDS #: 80307

SECTION X - MISCELLANEOUS

Do not transfer contents to bottles or other unlabeled containers. Do not store in high temperature (above 100F or 38C) environment. Keep from freezing.

KEEP OUT OF THE REACH OF CHILDREN

KEY CODE

N/A = Not Applicable

N/E = Not Established

ACGIH = American Conference of Governmental Industrial Hygienists

OEL= Occupational Exposure Limits

PEL = Permissible Exposure Limit

TWA=Time Waited Average

IARC = International Agency for Research on Cancer

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

The identities of ingredients are withheld as proprietary information. The information on this data sheet represents our best opinion as to the proper use and handling of this product under normal conditions, based upon information compiled from sources considered to be dependable. It is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. It is the user's responsibility to determine the suitability of this product for a specific purpose and to adopt such safety precautions as may be necessary. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.

BEFORE USING ANY PRODUCT, READ THE LABEL.